

## Terminal Tractor/Yard Spotter

Used Yard Spotter Virginia - Tow tractors, also called tow tugs or towing tractors are popular for moving loads horizontally in airports, arenas, warehouses, manufacturing plants and other large buildings. These machines can tow numerous trailers in a train or snake-like formation. Certain tow tractors can transport helicopters and giant airplanes for the purpose of positioning inside and outside airport hangars and terminals. Tractive effort is how these machines transport loads. Tractive effort refers to the total amount of traction a vehicle deploys on the ground. The heavier the load is, the more tractive effort is needed. The tow tractor lifts a portion of the load during towing while ensuring the wheels on the load still remain on the ground. The load is partially lifted by use of the tow tractor's hydraulic mast which is specifically designed to produce downforce on the drive wheel immediately beneath it, increasing the tractive effort. The tow tractor is capable of transporting very heavy and large loads thanks to the traction it provides. **Types of Tow Tractors** Two types of towing tractors include heavy-duty tow tractors and load carriers. Load Carriers Industries such as e-commerce, manufacturing, and airport baggage and parcel systems must regularly move many individual and varying sized items to or from a single location. Tow tugs and load carriers easily transport single items that have been deposited on wheeled platforms and move them with ease. Load carrier tow tractor models are categorized in the material handling equipment that covers cranes, forklifts and pallet jacks. These units only transport loads at ground level and do not lift or lower items from shelving or off the ground. In order to be ready for transport, items must be secured on a wheeled platform or already on wheels to use the tow tractor. The wheeled platforms are called bogies, trollies or skates. The tow tractor attaches to the trolley and operates similarly to how train cars are attached to a locomotive. Typically, the tow tug features a steel coupling male-end that attaches to a female-end on the trolley's front. The back of the trolley has a male-end steel coupling that can then be used to attach multiple trollies onto a single tow tug, transporting all the trollies in a train-like formation. Tow tractors are capable of moving many machines in a variety of conditions. Trolley types differ to provide customization options. Most trollies types are compatible with each other, meaning they can be connected together. This means several different types of trollies can be used in a single train allowing greater flexibility for operations. Load carrier tow tractors deliver a clear view for the operator which can be better than relying on forklifts. Further, load carrier tow tractors tow their trollies behind them in a forward-only direction which decreases the safety concerns created by forklifts operating in reverse. This is vital for safety-sensitive places including airports and manufacturing facilities. It is more economical to tow multiple items when possible with a tug than using a forklift truck to transport single items. They are safe and easy to maneuver. One benefit of these tow tugs is that an operator usually does not require a license. This is because the load is not lifted from the ground so it does not fall under the usual restrictions and licensing required of standard forklifts, cranes and other load lifting equipment. There are three kinds of load carrier tow tractor units to choose from; pedestrian, stand-in and rider-seated.

**Pedestrian Tow Tractors** A walk-behind model that can transport wheeled loads is called a pedestrian tow tractor. These machines may go by the names of electric hand tug, electric tugger, electric tug or tow tractor. These machines are simple to use, extremely maneuverable and very compact. **Stand-in Tow Tractors** Popular for industries that conduct order picking and horizontal transport for manufacturing, the stand-in tow tractors are the best design. They provide a secure platform for the driver to operate while still having a smaller footprint than that of the rider-seated tow tractors. **Rider-Seated Tow Tractors** Similar to stand-in tow tractors, rider-seated units have a seated operator platform. Rider-seated models are used for moving loads longer distances. They are popular for airport luggage transport to move checked baggage from the check-in counter to the aircraft parked at the terminal. Rider fatigue is decreased with sit-down units for more efficiency and productivity. **Heavy Duty Tow Tractors** In the aviation industry, large passenger and cargo planes usually employ the concept of pushback. Pushing an aircraft back from the airport terminal without

using the aircraft's own power is the pushback concept. This pushback process is done by using specially designed heavy duty tow tractors called pushback tractors or pushback tugs. Pushback tugs feature a low-profile enabling them to travel under the aircraft's nose for easy attachment. Enough ground friction is required to move the weighted aircraft, so these models need to be heavy themselves. Large aircraft tractors can weigh as much as fifty-four tons. These models have a driver's cab that has the option of being raised or lowered during reverse for better visibility. The unit is called a pushback tow tractor or pushback tug but it is additionally used to move aircraft in situations where taxiing is not safe or practical including into and outside of aircraft maintenance. The pushback tow tractors come in two subtypes, the towbarless and the conventional. Conventional Pushback Tow Tractors Conventional tugs use a tow bar to connect the tug to the nose landing gear of the aircraft. The tow bar is laterally fixed at the nose landing gear; however, it is possible to make height adjustments with slight vertical movements. At the end that attaches to the tug, the tow bar may pivot freely laterally and vertically. In this manner, the tow bar acts as a large lever to rotate the nose landing gear. Every aircraft has a special tow fitting and the towbar functions as an adapter between the fitting on the landing gear and the standard-sized tow pin. On heavy towbars for large aircrafts, the towbar rides on its own wheels when not connected to an aircraft. The wheels are attached to a hydraulic jacking mechanism which can lift the towbar to the correct height to mate to both the airplane and the tug, and once this is accomplished the same mechanism is used in reverse to raise the tow bar wheels from the ground during the pushback process. The towbar can be connected at the front or the rear of the tractor, depending on whether the aircraft will be pushed or pulled. Towbarless Pushback Tow Tractors Towbarless tractors do not use a towbar; they scoop up the nose landing gear and lift it off the ground, allowing the tug to maneuver the aircraft. This design facilitates higher speeds greater aircraft control and can eliminate the necessity of having a worker inside of the cockpit to apply the brakes. As there is no need to maintain numerous towbars, simplicity is the main advantage of this unit. Greater control and responsiveness while moving the aircraft is achieved with this direct connection of the tug to the landing gear.